

FabriTac is a removable adhesive fabric that can be mounted to any surface and repositioned countless times while retaining its adhesion without leaving a residue. FabriTac's unique coating is quick drying, water resistant, and provides superb image quality, color gamut and resolution with eco solvent, latex, solvent, and UV inks. FabriTac's unique opaque properties prevent translucency problems associated with comparable products. Available in 42", 54", and 60" widths.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	Polyester	Polyester
Yarn dtex	DIN EN ISO 2060	166 x 166 dtex	150 x 150 denier
Adhesive	White Repositionable Adhesive		
Total Weight	ISO 534	350g/m ²	10.3 oz/yd ²
Release Film	Paper Liner 100g (Both sides PE)		
Storage Recommendations	<ul style="list-style-type: none"> •All Ultraflex materials should be stored in their original packaging. •FabriTac should be stored in temperatures between 10° and 20° Celsius, and a relative humidity of 20% - 60%. 		

Applications

	Outdoor Advertising	Banner	Floor Decals	Posters	Stickers	Wall Graphics	POP/POS
Applications	■	■	■	■	■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■			

Available Sizes

Metric (m)	English (inches)
1.06,1.37,1.52	42, 54 ,60

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)