

UltraMesh 100 is a 10 oz. PVC coated polyester scrim mesh banner material. Its basket weave appearance allows 30% air-flow through making it ideal for large building, stadium and fence wraps. UltraMesh 100 can be printed on both sides with solvent and UV printers that have mesh kits. It is available in a 126" and 196" width.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	Polyester	Polyester
Yarn dtex	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier
Type of Coating	N/A	PVC	PVC
Total Weight	DIN EN ISO 2286-2	340 g/m <sup>2</sup>	10 oz/yd <sup>2</sup>
Tensile Strength	DIN EN ISO 1421	204 x 184 N/5cm	23 x 21 lbs/in
Tear Strength (warp/weft)	DIN 53363	2500 x 1300 N/5cm	285 x 148 lbs/in
Flame Resistance	DIN 75200	NFPA701, Title 19, CSFM, B1	
Low Temperature (No Crack at:)	ISO 1876	Low at -30°C	Low at -22°F
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes
Air Permeability	ISO 9237	1580 liter/m <sup>2</sup> /sec	
Fungus Resistant	ASTM G21	Treated	

### Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications		■			■		

### Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	□	■		■		

### Available Sizes

Metric (m)	English (inches)
3.20, 5.00	126, 196

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)