

Technical Data Sheet UltraMesh[®] Plus

UltraMesh Plus is an 8 oz. coated polyester scrim mesh banner material. This economical light weight material can be printed on one side and allows 37% air-flow through making it ideal for building, stadium and fence wraps. UltraMesh Plus can be printed with solvent and UV printers that have mesh kits. This product is also available with a PVC backer that peels off after printing called Strip Mesh Plus. It is available in a 126" and 196" width.

Material Details

| CHARACTERISTICS | TEST METHOD | METRIC | ENGLISH | |
|--------------------------------|-------------------------|----------------------------------|----------------------|--|
| Support Cloth | DIN 60001 | Polyester | Polyester | |
| Yarn dtex | DIN 53830 | 1100 x 1100 dtex | 1000 x 1000 denier | |
| Type of Coating | N/A | PVC | PVC | |
| Total Weight | DIN EN ISO 2286-2 | 280 g/m ² | 8 oz/yd ² | |
| Tensile Strength | ASTM D 751 :2006, C.R.E | 1400 x 1400 N/5cm | 160 x 160 lbs/in | |
| Tear Strength (warp/weft) | ASTM D 4830:1988 C.R.E | 300 x 300 N/5cm | 34 x 34 lbs/in | |
| Flame Resistance | DIN 75200 | NFPA701, Title 19, CSM, ASTM E84 | | |
| Low Temperature (No Crack at:) | ISO 1876 | -30° C -22° F | | |
| RF Weldable (Heat Sealable) | DIN 53354 | Yes | | |
| Air Permeability (200 Pascal) | ISO 9237 | 2650mm/sec | | |
| Fungus Resistant | ASTM G21 | Treated | | |

Applications

| | Back-lit | Banner | Billboard | Blockout | Building Wrap | Display Systems | Truckside |
|--------------|----------|--------|-----------|----------|------------------|--------------------|-----------|
| Applications | | | | | | | |

Ink Printability

| Solvent | Eco Solvent | UV | Latex | Screen Printing | Dye Transfer | Dye Direct |
|---------|----------------|----|-------|--------------------|-----------------|---------------|
| | | | | | | |

Available Sizes

| Metric (m) | English (inches) |
|------------|------------------|
| 3.20, 5.00 | 126, 198 |

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

www.ultrafleXX.com Updated: 02/2012 Ultraflex Headquarters 1578 Sussex Turnpike, Building 4 Randolph, NJ 07869 P. 973-627-8608 F. 973-627-8506

Ultraflex Europe Ltd.

Unit 2Hardwick Rd Industrial Park Great Gransden Bedfordshire, England SG193BJ P. +44 1767 677100 F. +44 1767 677190 Ultraflex Mexico

Avena 316-B Col. Granjas Mexico Mexico City, 08400 P. +52 5531-823-632 F. +52 5558-037-809