

## Technical overview of the Mimaki Kebab and Kebab MkII options

|                                 |                           | <b>Kebab</b>                      | <b>Kebab MKII</b>                 | <b>Kebab MKII L</b>               |
|---------------------------------|---------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| <b>Part number</b>              |                           | OPT-J0350                         | OPT-J0428                         | OPT-J0427                         |
| <b>Supported machines</b>       |                           | UJF-6042, UJF-3042 HG             | UJF-3042 MkII                     | UJF-6042 MkII, UJF-7151 plus      |
| <b>Maximum media rotation</b>   |                           | 360° or more (no limitation)      | 360° or more (no limitation)      | 360° or more (no limitation)      |
| <b>Rotation method of media</b> |                           | Friction of roller                | Friction of roller                | Friction of roller                |
| <b>Media shape</b>              |                           | Cylindrical                       | Cylindrical                       | Cylindrical                       |
| <b>Media size</b>               | <b>Small Diameter</b>     | .39 – 2.52 inches (10 -64.2mm)    | .39 – 2.52 inches (10 -64.2mm)    | .39 – 2.52 inches (10 – 64.2mm)   |
|                                 | <b>Large diameter</b>     | 2.53 – 4.33 inches (64.3 – 110mm) | 2.53 – 4.33 inches (64.3 – 110mm) | 2.53 – 4.33 inches (64.3 – 110mm) |
|                                 | <b>Width</b>              | 1.18 – 12.99 inches (30 – 330mm)  | 1.18 – 12.99 inches (30 – 330mm)  | 1.18 – 23.62 inches (30 – 600mm)  |
| <b>Print area</b>               | <b>Feed (X) direction</b> | 360° or more (no limitation)      | 360° or more (no limitation)      | 360° or more (no limitation)      |
|                                 | <b>Feed (X) direction</b> | 12.99 inches (300mm) or less      | 12.99 inches (300mm) or less      | 23.62 inches (600mm) or less      |
| <b>Max media weight</b>         | <b>Small Diameter</b>     | 4.4 lbs (2.0kg) or less           | 3.3 lbs (1.5kg) or less           | 3.3 lbs (1.5kg) or less           |
|                                 | <b>Large diameter</b>     | 4.4 lbs (2.0kg) or less           | 4.4 lbs (2.0kg) or less           | 4.4 lbs (2.0kg) or less           |
| <b>Interface</b>                |                           | Dedicated connector               | Dedicated connector               | Dedicated connector               |
| <b>Weight</b>                   |                           | Approx. 6.6 lbs (3kg)             | Approx. 6.6 lbs (3kg)             | Approx. 13.22 lbs (6kg)           |
| <b>Dimensions (W x D x H)</b>   |                           | 16.14 x 13.4 x 2.24 inches        | 14.4 x 11.8 x 1.9 inches          | 26.53 x 11.8 x 1.9 inches         |
|                                 |                           | 410 x 340 x 57mm                  | 366 x 301 x 50mm                  | 674 x 301 x 50mm                  |